Magellan 1500i OEM

Magellan 1500i, Black, OEM Configuration, 2D	MG1503-30200
Magellan 1500i, Black, OEM Configuration, 2D, USB A Cable	MG1503-30200-0200
Magellan 1500i, Black, OEM Configuration, 2D, Wall Mount Kit, USB A Cable	MG1503-30250-0200

EASEOFCARE AGREEMENTS

MAGELLAN 1500i EofC 5 DAYS RENEWAL	ZSN5M1500R1
MAGELLAN 1500i EofC, 2 DAYS COMPREHENSIVE, 3 YEARS	ZSC2M150031
MAGELLAN 1500i EofC, 2 DAYS COMPREHENSIVE, 5 YEARS	ZSC2M150051
MAGELLAN 1500i EofC, 2 DAYS COMPREHENSIVE, RENEWAL	ZSC2M1500R1
MAGELLAN 1500i EofC, 5 DAYS, 3 YEARS	ZSN5M150031
MAGELLAN 1500i EofC, 5 DAYS, 5 YEARS	ZSN5M150051
MGL 1500i EofC OVERNIGHT REPLACEMENT, COMPREHENSIVE, 3 YEARS	ZSC1M150031
MGL 1500i EofC OVERNIGHT REPLACEMENT, COMPREHENSIVE, 5 YEARS	ZSC1M150051
MGL 1500i EofC OVERNIGHT REPLACEMENT, COMPREHENSIVE, RENEWAL	ZSC1M1500R1

CABLES

Cable, IBM USB, Power Off Terminal, Straight, 2 m	8-0754-07
Cable, IBM, USB, Power Off Terminal, Straight, 3.66 m	8-0754-13
Cable, RS AUX, RJ10P, Straight, 2 m	90A052346
Cable, RS-232 9D S, External Power, SHT/OM, 600mm	90A052369
Cable, RS-232, External Power, 9D, S, 2 m	8-0751-11
Cable, RS-232, Ruby Verifone, 8RJ, P, External Power, Straight, 2 m	8-0751-16
Cable, RS-232, Wincor w/DTR, 2 m	8-0751-10
Cable, USB, OEM, Power Off Terminal, EAS, 2 m	90A052337
Cable, USB, Power Off Terminal, Coiled, 2.44 m	8-0754-15
Cable, USB, Power Off Terminal, Coiled, 3.6 m	90A052364
Cable, USB, Series A, Power Off Terminal, 1 m	90A052363

Cable, USB, Series A, Power Off Terminal, EAS, 2 m	90A052336
Cable, USB, Series A, Straight, 3.66 m	8-0754-14
Cable, USB, Type A, Power Off Terminal, 2 m	8-0754-12
Cable, USB+ Power Off Terminal, Coiled, 3.65 m	90A052351

MOUNTS/STANDS		
	Round Stand, Black Base, Black Scanner	90ACC0400
	Round Stand, Silver Base, Black Scanner	90ACC0402
	Round Stand, Silver Base, White Scanner	90ACC0401
	Wall Mount Kit, Black	90ACC0382

POWER SUPPLIES/CORDS	
Power Cord, 2-Pin, AU	90ACC0316
Power Cord, 2-Pin, China	90ACC0311
Power Cord, 2-Pin, EU	90ACC1885
Power Cord, 2-Pin, Japan	90ACC0312
Power Cord, 2-Pin, UK	90ACC1887
Power Cord, 2-Pin, US	90ACC1886
Power Supply, 5VDC, ready to accept 2 pin power cord or alternatively an adapter power plug (not included order separately)	90ACC0287

SOFTWARE	
API enabling FRS device integration for real-time tracking, connectivity and battery monitoring, diagnostics, anomaly detection, RMA/Ease-of-Care integration, centralized firmware control, advanced configuration, automation, and policy enforcement.	ZSIOTAPIFRS
IoT Essential Package for FRS Devices - Real-time tracking, connectivity and battery monitoring, system diagnostics, anomaly detection, RMA management, and Ease-of-Care integration for optimized FRS device fleet management	ZSIOTESSFRS
IoT Professional Package for FRS Devices -Centralized firmware management, advanced device configuration (scan modes, symbology, power settings), scheduled automation, and policy enforcement for compliant and optimized FRS devices performance	ZSIOTPROFRS